



2RXX-20

2RXX-I-20

项目 Item	规格 Specification								单位 Unit
	2R75 -20	2R90 -20	2R150 -20	2R230 -20	2R350 -20	2R470 -20	2R600 -20	2R800 -20	
	2R75 I-20	2R90 I-20	2R150 I-20	2R230 I-20	2R350 I-20	2R470 I-20	2R600 I-20	2R800 I-20	
标称直流击穿电压 Nominal DC Spark-over Voltage (100V/S)	75 ± 20%	90 ± 20%	150 ± 20%	230 ± 20%	350 ± 20%	470 ± 20%	600 ± 20%	800 ± 20%	V
最大冲击击穿电压 Maximum impulse spark- over voltage (1KV/us)	600	600	600	650	700	800	1000	1200	V
耐冲击电流 (短波) Impulse discharge current (8/20us, 10 times)	20	20	20	20	20	20	20	20	KA
耐冲击电流 (长波) Impulse discharge current (10/1000us, 300 times)	100	100	100	100	100	100	100	100	A
耐交流电流 AC discharge current (50Hz, Is, 10 times)	20	20	20	20	20	20	20	20	A
最小绝缘电阻 Minimum insulation resistance	1000	1000	1000	1000	1000	1000	1000	1000	MΩ
最大极间电容 Maximum capacitance (1MHZ)	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	pF

75V、90V、150V、230V、350V 主要用于一级信号防护

470V、600V、800V 主要用于AC电源防雷(高辉光电压型)